MATERIAL SAFETY DATA SHEET

SECTION I—PRODUCT IDENTIFICATION

MANUFACTURERS' NAME: ADVANCED COATINGS & CHEMICALS

Subsidiary of Olin Hunt Specialty Products, Inc.

4343 Temple City Blvd. Temple City, CA 91780 DATE OF PREPARATION:

8-24-87

EMERGENCY PHONE NO: (818) 579-6270

VOC 8

860 Grams/ Liter

PRODUCT FORMULA: 30C-1					*	
1110000111711112.	SPRAY TYPE REDU	CER				
PRODUCT CHEMICAL FAMILY: 0	RGANIC SOLVENT	*****	NIO INOB	FOIENTS		<u></u>
	SECTION II-		POSURE LIN		1400 1470	
INGREDIENTS	CAS NUMBER	OSH PEL	IA T	ACGIH TLV	IARC, NTP OSHA HAZARD EVALUATION	
METHYL ETHYL KETONE	78-93-3	200ppm		200ppm	NON-CARCINOGENIC NARCOTIC	
METHYL ISOBUTYL KETONE	108-10-1	200ppm		200ppm	NON-CARCINOGENIC	
COLUENE	108-88-3	100ppm	1	00ppm	NON-CARCINOGENIC NARCOTIC NON-CARCINOGENIC	
ETHYL 3-ETHOXY PROPIONATE	763-69-9	NOT EST	r. N	OT EST.	IRRITANT, MILDLY NON-CARCINOGENIC	TOXIC
n-BUTYL ACETATE	123-86-4	150ppm		150ppm	NARCOTIC NARCOTIC	
					·	
	SECTION	ON III—PH	YSICAL D	ATA		
BOILING POINT: 175°F				GRAVITY:	0.86	<u></u>
VAPOR DENSITY (AIR = 1): HEAVIER				LE BY VOLUME:	100%	
SOLUBILITY IN WATER: NEGLIGIBLE		EVAPORATION RATE:		FASTER		
VAPOR PRESSURE: @20°C43.39		_mm.Hg.	(BUTYL ACETATE = 1)			
	SECTION IV—FIR	RE AND EXI	PLOSIVE	HAZARD DAT	A	
FLASH POINT: 20	ºF. TCC_LEL:_	1.05		% by Volume_UE	L: 10.0	% By Volum

EXTINGUISHING MEDIA: Foam, Dry Chemical, CO² and/or Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS:

During a fire, irritating and toxic gases and smoke are present from decomposition. Isolate from heat, sparks and open flames. Closed containers may burst when exposed to extreme heat. Vapors form an explosive mixture in air between the upper and lower explosive limits.

SPECIAL FIREFIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus should be worn by firefighters.

SECTION V—HEALTH HAZARD DATA

EFFECTS OF ACUTE OVEREXPOSURE:

Eyes: Can cause severe irritation, redness, tearing and blurred vision.

Skin: Prolonged or repeated contact can cause irritation. Defatting to skin.

Inhalation: Dizziness, breathing difficulty, headaches and loss of coordination.

Ingestion: Damage to throat and esophagus, vomitting and diarrhea.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Asthma, respiratory tract irritation, dermatitis. Kidney and liver problems, conjunctivitis.

PRIMARY ROUTES OF ENTRY: Dermal, inhalation, ingestion.

EMERGENCY AND FIRST AID PROCEDURES:

Eye Contact: Flush with large amounts of water for 15 minutes.

Skin Contact: Wash thoroughly with soap and water. See a doctor

Inhalation Over Exposure: Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention.

Ingestion: Do not induce vomitting. Can cause chemical pneumonitis and pulmonary edema. Contact physician immediately.

OTHER HEALTH HAZARDS: EFFECTS OF CHRONIC OVEREXPOSURE:

EYES: Blurred vision. Conjuctivitis. SKIN: Sensitization, dermatitis. INHALATION: Asthma-like symptoms.

Central nervous system effects. INGESTION: Damage to throat. Possible kidney and liver impairment.

SECTION VI—REACTIVITY DATA

STABLITY: Stable

RDOUS POLYMERIZATION: Will not occur.

HALARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide; carbon dioxide, oxides of nitrogen, various hydrocarbon and acrid fumes.

CONDITIONS TO AVOID:

Excessive heat, poor ventilation. Corrosive atmosphere, excessive aging, sparks and open flames.

INCOMPATIBILITY (MATERIAL TO AVOID):

Alkaline materials, strong acids and oxidizing materials.

SECTION VII—SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate ignition sources; provide good ventilation; dike spill area and add absorbent material to spilled liquid. Thoroughly wet with water and mix.

WASTE DISPOSAL METHOD:

Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state and federal hazardous waste regulations before disposing into approved hazardous wastes landfills. Obey relevant laws.

SECTION VIII—SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

When spraying and/or printing this material, use a NIOSH-approved cartridge respirator or gas mask suitable for airborne mists and vapor concentrations below the time-weighted threshold limit values. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

VENTIL ATION

General mechanical ventilation or local exhaust should be suitable to keep vapor concentration below TLV. Ventilation equipment must be explosion-proof.

PROTECTIVE GLOVES: Impermeable chemical handling gloves for skin protection.

EYE PROTECTION: Use chemical safety glasses, goggles and face shields for eye protection.

OTHER PROTECTIVE EQUIPMENT:

Use impermeable aprons and protective clothings when ever possible to prevent skin contact. The use of head caps when ever possible is strongly recommended.

HYGIENIC PRACTICE: Eye washes and safety showers in the work palce is recommended.

SECTION IX—SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Use non-sparking utensils when handling this material. Avoid hot metal surfaces. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

OTHER PRECAUTIONS:

Smoking in areas where this material is used should be strictly prohibited. Tools used with this material should be aluminum, brass or copper. Plastic tools should not be used. Since emptied containers retain product residues, (vapors, liquid and/or solid) all hazard precautions should observed.

SECTION X—TRANSPORTATION DATA									
PROPER SHIPPING NAME:	FLAMMABLE	LIQUID	UN1993						
DOT CLASSIFICATION:	FLAMMABLE			DOT LABEL:	RED				
PRECAUTIONS TO BE TAKEN	IN TRANSPORTA	ATION:		Refe	r to Section IX				

NOTE: THIS INFORMATION IS ACCURATE TO THE BEST KNOWLEDGE OF ADVANCED COATING & CHEMICALS COMPANY, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

BOE-C6-0226922